


# Care Instructions Resysta Facade



## Schematic presentation – color application



### Resysta RFS sealed, untreated Resysta, or color-glazed surface

**MAINTENANCE:** Finishing of the sealing in case of external mechanical damages is possible and recommended for aesthetic reasons only. Even after ten years, the surface displays barely visible changes in color. In fact, the color becomes more intense, but not more than approximately 10%. No greying (unlike wood).

**CLEANING:** Resysta RFS seals the surface. Thanks to this sealed structure, dirt particles only adhere to the surface and can be removed easily with a gentle jet of water (i.e. garden hose) or with a soft brush.

**CARE:** Special care is not necessary (except for cleaning). Therefore, elaborate sanding and painting of the facade is not required in the long run.

### Resysta FVG glazed color scheme color concept

**MAINTENANCE:** Minor color changes are possible. Depending on weather conditions, a slight fading of the color can occur. The glaze does not seal the surface. Further color application is possible at any time. Over the years, a change in color is less visible with highly-pigmented glazes in comparison to glazes with less pigment-content. No greying (unlike wood).

**CLEANING:** The surface is colored by means of transparent-colored Resysta FVG glazes. Dirt, caused by environmental influences, may deposit through the open structure. This can, however, easily be removed by means of a gentle jet of water (i.e. garden hose) or with a soft brush. Tenacious dirt can also be removed by gentle sanding.

**CARE:** The glaze can be reconditioned in diluted form (for example: 3:1 mixture ratio with water). Beforehand, the surface has to be carefully cleaned and gently sanded.

### Resysta untreated

**MAINTENANCE:** Maintenance of the untreated Resysta material is not necessary.

**CLEANING:** Due to the open structure of the surface, dirt can deposit (for instance, dirty water stains). As these only adhere to the surface, they can be removed by means of a gentle jet of water (i.e. garden hose), with a soft brush or high-pressure jet (appropriate distance, approx. 30 cm). Tenacious dirt can also be removed by gentle sanding.

**CARE:** Special care is not required (except for cleaning). Fading in comparison to the original color shade is typical for this material, if it is not sealed. This however has no impact on the durability of the material. No greying (unlike wood).

#### GENERAL RECOMMENDATIONS:

- We recommend a yearly inspection of the facade for damages.
- Resysta FVG and Resysta RFS were especially developed for Resysta and are perfectly adapted for this material. Only these surface treatments may be employed exclusively.
- Since soiling can occur especially in areas exposed to direct spray-water and in the gable area, these surface areas should be sealed by employing Resysta RFS.

**25 YEARS  
GUARANTEE\***

- no swelling
- no cracking
- no splintering
- no rotting

**Resysta®**  
THE BETTER WOOD

\*For the fulfillment of material guarantee claims, surface protection treatment is not needful!